

SUBMERSIBLE SEWAGE PUMP



*Helps world to
save energy...*



APPLICATIONS

- ✿ Drainage and sewerage system
- ✿ Storm water
- ✿ Effluent with slurry and solids
- ✿ Transfer of suspended solids
- ✿ Raw water pumping application





**PERFORMANCE CHART
ARVIND MAKE NON CLOG SEWAGE SUBMERSIBLE PUMP**

Sr.No.	Model	HP	Outlet size Mm	Solid Size mm	H E A D I N M E T E R													Weight In Kgs			
					2	4	6	8	10	12	15	18	20	25	28	32	40				
NON CLOG SEWAGE PUMP					1440 RPM/3 PHASE /AC SUPPLY /50HZ																
01	APNC20	2.0	75	65	1100	1050	950	750	650	550	Shut Off Head -13.5 Mtr					95					
02	APNC30	3.0	75	65	1100	1050	950	750	650	550	Shut off Head-13.5 Mtr					95					
03	APNC30A	3.0	75	65	1490	1380	1150	825	530	Shut off Head-12.5 mtr					95						
04	APNC40	4.0	75/100	65	1580	1420	1250	960	590	Shut off Head-13 .0 Mtr					125						
05	APNC50	5.0	100	75	1450	1380	1260	1100	900	750	250	Shut off Head-16.5 Mtr				135					
06	APNC50A	5.0	100	75	1750	1620	1435	1200	860	435	Shut Off head- 14.0 Mtr					140					
07	APNC75	7.5	100	80	1890	1750	1580	1390	1150	780	450	Shut off head -17.0 Mtr				145					
08	APNC100	10.0	100	80	2180	1990	1890	1750	1600	1260	870	250	Shut Off Head-20.0 Mtr				158				
09	APNC100A	10.0	100	80	2800	2360	2150	1980	1200	600	Shut Off Head- 14.5 Mtr					165					
10	APNC125	12.5	100	80	3450	2980	2650	2360	2250	1400	1100	800	Shut off Head-21.0 Mtr				170				
S.H.11	APNC150	15.0	100	80	3600	3350	3200	3000	2800	2600	2100	1650	1200	Shut Off Head-26.0 Mtr							
12	APNC125	12.5	125	80/100	4200	3950	3250	2700	1950	800	Shut Off Head-14.5 Mtr					270					
13	APNC150A	15.0	125	80	4700	4250	3900	3600	3150	2000	1600	1050	800	Shut off Head-23.5 Mtr				290			
14	APNC150B	15.0	125	80/100	5000	4790	4450	4070	3750	3450	2650	1200	Shut Off Head-20.0 Mtr				295				
15	APNC200	20.0	125/150	80/100	5200	4900	4680	4200	3853	3500	3350	2460	1950	788	S.H.28.0 Mtr				310		
16	APNC200A	20.0	125/150	80/100	6500	5800	5350	5100	4700	4300	2860	1450	Shut off head-22.0 Mtr					320			
17	APNC250	25.0	125/150	80/100	7800	7100	6200	5600	5200	4500	4200	2860	1450	Shut Off Head-25.0 Mtr				335			
18	APNC300	30.0	125/150	80/100	8100	7500	6900	6200	5600	5000	4400	3100	2750	1100	S.H.29.0 Mtr				340		
19	APNC350	35.0	150	80/100	8500	7800	7200	6500	6000	5400	5000	4200	3500	2400	1100	S.H. 32 Mtr				355	
20	APNC400	40.0	150/200	100		8500	7800	7200	6700	6100	5500	4700	4000	2800	1800	800	S.H.37				450
21	APNC500	50.0	150/200	100		9800	8800	8200	8000	7300	6500	6000	5300	4000	3200	2100	S.H.42.5				500
22	APNC550	55.0	150/200	100		10800	9400	9050	8500	7900	7100	6700	5900	5000	4010	2750	1400(S.H.45 Mtr				535
23	APNC600	60.0	150/200	100			10800	9600	8900	8200	7600	7200	6400	5500	4200	3100	1400 S.H..47 Mtr				580
24	APNC650	65.0	150/200	1001			12000	11400	10800	9070	8400	7800	7200	6400	5000	3250	1570 S.H. 48 Mtr				610
NON CLOG SEWAGE PUMP-					2850 RPM /3 PHASE /AC SUPPLY/50 HZ																
					15	20	25	30	35	40	45	50	60	65	70		80				
01	APNC30B	3.0	75	20/30	300	100	Shut off Head – 32.0 Mtr										70				
02	APNC50B	5.0	75	20	500	300	180	Shut off Head – 27.5 Mtr										80			
03	APNC75A	7.5	75	25	750	550	400	280	Shut off Head –33.0 Mtr										110		
04	APNC100B	10.0	75	35	1100	980	800	350	200	Shut off Head – 37.0 Mtr										124	
05	APNC125A	12.5	100	35	1250	1100	1000	800	650	500	250	Shut Off Head – 47.5 Mtr					145				
06	APNC150A	15.0	100	35	1350	1350	1250	1000	900	680	350	180	Shut off Head – 52.0 Mtr					280			
07	APNC200B	20.0	100	35		1500	1480	1400	1250	1050	800	590	300	200	Shut off Head – 67.0 Mtr				298		

- All Model are fitted with Bi-directional mechanical seal, Moisture sensor, Thermal sensor
- We can supply pumps in various materials depending upon the liquid quality.